



## SolSafe<sup>®</sup> 245 is our ultimate solvent for industrial and precision cleaning

SolSafe<sup>®</sup> 245 is the **ULTIMATE SOLVENT** for industrial and precision parts cleaning. It effectively **removes oil, grease, asphalt, bitumen, and the toughest hydrocarbon contaminants** without leaving a residue.

SolSafe 245's proprietary **full-strength** formulation is **non-hazardous, partially biodegradable, and non-toxic** without compromising effectiveness. It is an excellent replacement for MEK, xylene, diesel, and other hazardous solvents for many industrial applications.

SolSafe 245 **lowers total cleaning cost.** The multi-purpose formulation helps reduce your inventory by replacing other harsh solvents. The lower

evaporation rate allows SolSafe 245 to penetrate for longer periods of time and **reduces total product use.**

**Non-Toxic**  
**Residue Free**  
**Non-Chlorinated**  
**Non-Aqueous**  
**Replaces Hazardous Solvents**  
**Fresh Scent**

### AVAILABLE PRODUCTS

Item #BF1022 - Case of 12 - 15 oz Aerosol Cans



## APPLICATIONS

- Metal parts degreasing and cleaning
- Surface preparation prior to painting
- Electrical parts degreasing and cleaning
- Removing adhesive residues
- Removal of all heavy hydrocarbon fouling
- Cleaning / degreasing without water



A WHOLLY OWNED  
SUBSIDIARY OF **REFINED**  
technologies



Replacing hazardous solvents without compromising effectiveness.

**BioChem Systems**  
480 Wildwood Forest • Suite 400  
Spring, Texas 77380  
cservice@biochemsys.com  
800-777-7870

### DIRECTIONS

1. Remove loose dirt and soil prior to cleaning.
2. Protect rubber parts, plastic and painted surfaces.
3. Shake can well before spraying.
4. Spray SolSafe<sup>®</sup> 245 directly on the surface to be cleaned. Hold can 18 to 24 inches away.
5. Let penetrate for 30 to 120 seconds.
6. Wipe dry as needed. (Drying process may be accelerated by heating parts with warm, dry air.) Water rinse is not required.
7. For tough deposits, repeat steps 1 through 6.

Item #	BF1022
Physical State:	Aerosol
Net Contents:	15 oz
Qty per Case:	12
Case Dimensions:	11.5"L x 9"W x 10.75"H
Case Weight:	16 lbs

Scent:	Light Clean Scent, Solvent
Color:	Clear/Colorless
Flash Point:	145°F (62.7°C)
Base Type:	Petroleum
Propellant:	Hydrocarbon / CO <sub>2</sub>
Spray Pattern:	Stream / Dispersed
Dielectric Strength:	49,000 v/cm
Solvency/KB:	106
VOC Content:	100%
pH:	N/A
Relative Evaporation Rate:	> 1
Relative Vapor Density:	0.78 - 0.82
Restricted from Sale:	None
California Prop 65 Warning:	None

**DANGER:** Extremely flammable aerosol. Contains gas under pressure: may explode if heated. May be fatal if swallowed and enters airways.

**PREVENTION:** Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

**RESPONSE:** IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.

**STORAGE:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

**DISPOSAL:** Dispose of contents / container to hazardous or special waste collection point, in accordance with local, regional, national and / or international regulation.

**EMERGENCY TELEPHONE NUMBER PERS:**  
(800) 633-8253

**KEEP OUT OF REACH OF CHILDREN  
FOR INDUSTRIAL USE ONLY**



A WHOLLY OWNED  
SUBSIDIARY OF 



Replacing hazardous solvents without compromising effectiveness.

**BioChem Systems**  
480 Wildwood Forest • Suite 400  
Spring, Texas 77380  
cservice@biochemsys.com  
800-777-7870