



TarBuster® is your ultimate solvent for quickly and safely removing asphalt, tack, and other tough contaminants.

TarBuster® was formulated for the toughest industrial cleaning tasks and **cuts cleaning time** so you can focus on more important things. In as little as 30 seconds after application, TarBuster starts dissolving the toughest residue.

TarBuster is the **ultimate safe solvent** for the refining and paving industries. The **full strength concentrate** safely penetrates, dissolves, and removes grease, slurry, bitumen, asphalt, tar, paraffins, and other heavy oils.

TarBuster is **water dilutable** for a wide range of uses, and can lower the number of solvents and safety data sheets needed in your facility. It's perfect for paving and roofing equipment, tankers, diesel engines, pipe and tank exteriors, tools, parts, and more. TarBuster is ideal for use in pump sprayers, hand wipe applications, and for other industrial applications.

Organic, biodegradable, non-toxic and non-corrosive – TarBuster is the perfect replacement for hazardous chlorinated solvents and petroleum distillate products that are traditionally used in industrial hydrocarbon removal and cleaning applications.

**Non-Toxic / Non-Corrosive
Biodegradable / Renewable
Non-Chlorinated
No Petroleum Distillates
Replaces Hazardous Solvents
Pine Scent**

AVAILABLE PRODUCTS

Item #BF1983 - 1 Gallon Can (4/cs)
Item #BF1984 - 5 Gallon Pail
Item #BF1985 - 55 Gallon Drum
Item #BF1986 - 275 Gallon Tote

APPLICATIONS

- Asphalt paving equipment and tools cleaning
- Roofing equipment and tools cleaning
- Tank cleaning
- Heavy degreasing
- Removal of heavy hydrocarbon fouling
- Oil and grease spill cleanup



A WHOLLY OWNED SUBSIDIARY OF **REFINED technologies**



Replacing hazardous solvents without compromising effectiveness.

BioChem Systems
480 Wildwood Forest • Suite 400
Spring, Texas 77380
cservice@biochemsys.com
800-777-7870

DIRECTIONS

1. Where applicable, remove loose dirt and soil from surface to be cleaned.
2. Apply directly to the surface. (see chart below)
3. Let penetrate for 30 seconds to 2 minutes.
4. Agitate with brush or wipe with cloth.
5. Rinse thoroughly with water or damp cloth.
6. Repeat steps 1 through 5, if necessary.

NOTE: TarBuster is NOT for use in vapor degreasing equipment. It is NOT necessary to heat TarBuster for effective cleaning / degreasing. This product should be kept from freezing and temperatures below 40°F. When using in a pump sprayer, please use Viton™ or Teflon™ seals to extend the life of the sprayer.

Cleaning Application	Ratio - TarBuster to Water
Asphalt, Mastics, Waxes, Adhesives, Cosmoline	Full Strength
Sludge, Heavy Grease	1:4
Cutting Oils, Light Grease and General Purpose Cleaning	1:10
Floor Mopping and Machine Cleaning	1:20

When diluting, please add TarBuster® to water for best results.

Item #	BF1983, BF1984, BF1985, BF1986
Physical State:	Liquid
Net Contents:	1 gal, 5 gal, 55 gal, 275 gal
Container Types and Weights:	Steel Can - 1 gal - 8.25 lbs
	Steel Pail - 5 gal - 42.5 lbs
	Steel Drum - 55 gal - 453.5 lbs
	Tote - 275 gal - 2113 lbs

Scent:	Floral Pine
Color:	Light Yellow
Flash Point:	130°F (54°C)
Base Type:	Terpenes
Solvency/KB	95
VOC Content (AQMD Method 24):	750 g/L (Undiluted)
pH:	7.5 - 8.5 (10% solution)
Relative Evaporation Rate:	< 1 (Water=1)
Relative Density:	0.863
Restricted from Sale:	None
California Prop 65 Warning:	Diethanolamine

DANGER: Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

PREVENTION: Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use explosion-proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Ground / bond container and receiving equipment. Avoid breathing mist / vapors / spray. Wash hands, forearms, and face thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves, protective clothing, chemical goggles, and

face protection. Read precautions and directions carefully before using.

RESPONSE: IF SWALLOWED: Immediately call a doctor or a poison center. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. If skin irritation or rash occurs: Get medical advice / attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice / attention. In case of fire: Use media other than water to extinguish.

STORAGE: Keep container tightly closed. Store locked up in a cool, well-ventilated place.

DISPOSAL: Dispose of contents / container to hazardous or special waste

collection point, in accordance with local, regional, national and / or international regulation.

EMERGENCY TELEPHONE NUMBER PERS:
(800) 633-8253



WARNING: This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY**



10292024



A WHOLLY OWNED
SUBSIDIARY OF
REFINED
technologies

Replacing hazardous
solvents without
compromising
effectiveness.

SMART
CHEMISTRY™

BioChem Systems
480 Wildwood Forest • Suite 400
Spring, Texas 77380
cservice@biochemsys.com
800-777-7870