



TarBuster® is your ultimate solution for quickly dissolving hardened asphalt, sealer, tack, emulsion, and more.

TarBuster® was designed to quickly penetrate and remove hardened asphalt, sealer, tack, emulsion, heavy grease, and more. TarBuster can drastically reduce the time and effort needed to clean and maintain your tools and equipment by making quick work of the toughest and heaviest asphalt-based deposits.

TarBuster is highly concentrated and fast-acting. In as little as 30 seconds after application, TarBuster will begin to dissolve any asphalt-based material and allow for easy removal with a scraper or water rinse.

TarBuster is industrial-strength, but is compatible with all metals and can be used to clean clear coated painted

surfaces. It is also safe for workers and is non-toxic, non-caustic, and biodegradable.

- Non-Corrosive / Non-Caustic**
- Non-Toxic / Biodegradable**
- Safe on All Metals**
- Safe on Clear Coat**
- Highly Concentrated**
- Fresh Scent**

AVAILABLE PRODUCTS
Item #BF1983 - 1 Gallon Can (4/cs)
Item #BF1984 - 5 Gallon Pail
Item #BF1985 - 55 Gallon Drum
Item #BF1986 - 275 Gallon Tote



APPLICATIONS

Surface cleaning of:

- Pavers
- Rollers
- Haulers
- Tack Trucks
- Sealing / Patching Equipment
- Hand Tools
- Concrete Surfaces

REMOVES

- Asphalt
- Tack
- Sealer
- Emulsion
- Heavy Oil & Grease



A WHOLLY OWNED SUBSIDIARY OF **REFINED technologies**

Replacing hazardous solvents without compromising effectiveness.

SMART CHEMISTRY

BioChem Systems
 480 Wildwood Forest • Suite 400
 Spring, Texas 77380
 cservice@biochemsys.com
 800-777-7870

DIRECTIONS

1. Where applicable, remove loose dirt and soil from surface to be cleaned.
2. Apply a light coating of TarBuster directly to the surface.
3. Let soak and penetrate for 5-30 minutes. Longer times are needed for heavier deposits.
4. Agitate with a brush or cloth for better penetration.
5. Rinse thoroughly with high-pressure water or wipe with damp cloth.
6. Repeat steps 1 through 5, if necessary.

NOTE: TarBuster is too strong to be used as a release agent for hot-mix asphalt or to flush lines. This product should be kept from freezing and temperatures below 40°F. When using in a pump sprayer, please use Viton™ or Teflon™ seals to extend the life of the sprayer. TarBuster can degrade plastics, rubber, and other sensitive parts over time. If applied to these surfaces, simply rinse with water to deactivate. TarBuster is safe on painted surfaces with a clear coat. Apply to the painted surface to be cleaned and then rinse or wipe clean before TarBuster dries to avoid any dulling or hazing. Nitrile gloves and eye protection are recommended when using TarBuster.

DANGER: Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

PREVENTION: Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use explosion-proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Ground / bond container and receiving equipment. Avoid breathing mist / vapors / spray. Wash hands, forearms, and face thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves, protective clothing, chemical goggles, and

face protection. Read precautions and directions carefully before using.

RESPONSE: IF SWALLOWED: Immediately call a doctor or a poison center. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. If skin irritation or rash occurs: Get medical advice / attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice / attention. In case of fire: Use media other than water to extinguish.

STORAGE: Keep container tightly closed. Store locked up in a cool, well-ventilated place.

DISPOSAL: Dispose of contents / container to hazardous or special waste

Item #	BF1983, BF1984, BF1985, BF1986
Physical State:	Liquid
Net Contents:	1 gal, 5 gal, 55 gal, 275 gal
Container Types and Weights:	Steel Can - 1 gal - 8.25 lbs
	Steel Pail - 5 gal - 42.5 lbs
	Steel Drum - 55 gal - 453.5 lbs
	Tote - 275 gal - 2113 lbs

Scent:	Floral Pine
Color:	Light Yellow
Flash Point:	130°F (54°C)
Base Type:	Terpenes
Solvency/KB	95
VOC Content (AQMD Method 24):	750 g/L (Undiluted)
pH:	7.5 - 8.5 (10% solution)
Relative Evaporation Rate:	< 1 (Water=1)
Relative Density:	0.863
Restricted from Sale:	None
California Prop 65 Warning:	Diethanolamine

collection point, in accordance with local, regional, national and / or international regulation.

EMERGENCY TELEPHONE NUMBER PERS:
(800) 633-8253



WARNING: This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY**



03122025



A WHOLLY OWNED
SUBSIDIARY OF
REFINED
technologies

Replacing hazardous solvents without compromising effectiveness.

SMART
CHEMISTRY™

BioChem Systems
480 Wildwood Forest • Suite 400
Spring, Texas 77380
cservice@biochemsys.com
800-777-7870